

Pos.	Stück	Leistungsbeschreibung	E-Preis	G-Preis
------	-------	-----------------------	---------	---------

10 1 **PRIODOOR – 90 Minutes
Fire Resisting Closure**

Single leaf and double leaf doors (fire resisting closures) with block frames and circumferential smoke seal, decorative surface or real wood veneer. With general building authority approval.

Function

- 90 minutes fire resistance, fire resistant
- T 90-RS classification
- Smoke-tight and tested for continuous operation
- Soundproofing 37 dB (1-leaf)

Construction

- Fire door with high mechanical resistance
- Standard door height up to 2,500 mm
- Standard double-leaf door width up to 2,500 mm
- Hydraulic door closer for automatic door closure
- Three-sided block frame, 55 mm thick and made of the same solid material
- Grooved door, closes flush with the block frame on both sides
- Circumferential and permanently elastic smoke seal
- Circumferential fire protection seal, automatically expands in case of fire
- 3D stainless steel bands, latch lock with double cylinder
- Smokeproof design with floor sealing

Material characteristic

- High density solid material with high mechanical resistance
- Standard HPL surface
- Standard design: white - similar to RAL 9016; Edges and chamfers darkly contrasted
- Green Building Declaration according to LEED and DGNB

Options and accessories

- Standardised colours - decor aluminium brushed; primer foil
- Surfaces in alternative RAL colours, decors or real wood on request
- Surface in stainless steel and thin sheet on request
- Double-leaf doors with asymmetrical door leaf division
- Extra wide frames according to requirements
- Floor seal, self-extending for smoke protection
- Flush fitted fire protection glazing
- Lock with panic release for emergency exits

PRIODOOR is offered on a project-by-project basis

Pos.	Stück	Leistungsbeschreibung	E-Preis	G-Preis
------	-------	-----------------------	---------	---------

Element-External dimension
(H x B) in mm:

Rough opening:
(H x B) in mm:

Surface:

Wall type:

Door hinge (DIN L / DIN R):

Number glas elements:

Dimension glas elements
(H x B) in mm:

Number fixed leaf:

Number active leaf:

Options:

Typ: PRIODOOR FSA 90

T 90-1-FSA "PRIODOOR T91"
T 90-1-RS-FSA "PRIODOOR T91"
T 90-2-FSA "PRIODOOR T92"
T 90-2-RS-FSA "PRIODOOR T92"

Fabrikat: PRIORIT AG
www.priorit.de
Tel.: +49 6181 3640-0
Fax : +49 6181 3640-230